

PCTINTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61K 7/06	A1	(11) International Publication Number: WO 95/20939 (43) International Publication Date: 10 August 1995 (10.08.95)
(21) International Application Number: PCT/US95/00983 (22) International Filing Date: 25 January 1995 (25.01.95) (30) Priority Data: 08/190,830 2 February 1994 (02.02.94) US 08/357,646 22 December 1994 (22.12.94) US (71) Applicant: THE PROCTER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US). (72) Inventors: COX, Bruce, Russell; 8071 Ivory Hills Drive, West Chester, OH 45069 (US). DODD, Michael, Thomas; 1210 Bobwhite, Edgewood, KY 41018 (US). (74) Agents: REED, T., David et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217 (US).		(81) Designated States: AU, BR, CA, CN, JP, KR, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>
(54) Title: HAIR CARE COMPOSITIONS CONTAINING LOW MELTING POINT FATTY ALCOHOL AND AN ETHYLENE OXIDE/PROPYLENE OXIDE POLYMER (57) Abstract <p>The present invention relates to hair conditioning compositions comprising from about 0.1 % to about 10 % by weight of a monohydric, fatty alcohol having a melting point of 30 °C or lower; from about 0.1 % to about 10 %, by weight of a polymer of ethylene oxide, propylene oxide, and mixtures thereof, having general formula (I), wherein R is selected from the group consisting of H, methyl, and mixtures thereof; and n has an average value of from about 2,000 to about 14,000; from 0 % to about 20 %, by weight, of a conditioning agent selected from the group consisting of cationic surfactants, cationic polymers, nonvolatile silicones, nonvolatile hydrocarbons, saturated C₁₄ to C₂₂ straight chain fatty alcohols, nonvolatile hydrocarbon esters, and mixtures thereof; and water. These hair care compositions provide a product with a thickened, cream emulsion or gel-type rheology having good wet hair feel, spreadability, and rinseability, as well as providing glossiness, hair alignment, volume reduction, and dry combing benefits.</p> <div style="text-align: right;">$\text{H}(\text{OCH}_2\text{CH})_n\text{--OH} \quad (\text{I})$<p style="text-align: center;"> R</p></div>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

HAIR CARE COMPOSITIONS CONTAINING LOW MELTING POINT
FATTY ALCOHOL AND AN ETHYLENE OXIDE/PROPYLENE OXIDE
POLYMER

5

TECHNICAL FIELD

The present invention relates to hair care compositions such as cream rinse emulsions, that enhance glossiness of the hair and provide dry combing benefits, containing low melting point fatty alcohols and particular water soluble, nonionic polymers.

10

BACKGROUND OF THE INVENTION

Scalp hair becomes soiled due to its contact with the surrounding environment and from sebum secreted from the hair follicles. The build-up of sebum and environmental soiling can cause the hair to have a dirty or greasy feel, and an unattractive appearance. In order to ameliorate these effects, it is necessary to shampoo the hair with regularity.

15

Shampooing the hair removes excess sebum and other environmental soiling but has disadvantages in that the hair can be left in a wet, tangled, and relatively unmanageable state. Shampooing can also result in the hair becoming dry due to the removal of natural oils or other hair moisturizing materials. After shampooing, the hair can also suffer from a perceived loss of "softness." Frequent shampooing also contributes to the phenomena of "split ends," particularly for long hair. Split ends refers to a condition wherein the ends of the hair are split into two or more shafts, resulting in a frizzy appearance.

20

25

A variety of approaches have been developed to condition the hair. These range from post-shampooing hair rinses, to leave-on hair conditioners, to the inclusion of hair conditioning components in shampoos. Although many consumers prefer the ease and convenience of a shampoo which includes conditioners, a substantial proportion of consumers prefer the more conventional conditioner formulations which are applied to the hair as a separate step from shampooing, usually subsequent to shampooing. These hair conditioners typically are formulated as a thickened product, such as a gel or cream, for ease of dispensing and application to the hair.

30

35

Consumers who have naturally coarse, wavy, or curly hair and wish to reduce these natural tendencies, may prefer conditioners which

provide shine, hair alignment, and decreased hair volume. In addition some consumers who have relatively straight hair desire volume reduction and greater alignment of the hair for enhanced glossiness and an orderly appearance of the hair.

5 Hair shine or "glossiness" is a desirable attribute which refers to the contrast between the specular and diffuse light reflected off hair fibers. This contrast creates a visual perception of "sheen" strongly associated with healthy hair. A conventional method for increasing hair shine is to treat the hair with compositions containing hydrocarbon oils
10 and fatty esters. Unfortunately, while these types of materials are effective for achieving their intended effect, they also tend to leave the hair feeling greasy or oily, and cause the hair to resoil relatively quickly.

 Improved glossiness, hair alignment, and volume reduction with relatively little greasy or oily feel when applied to the hair at relatively
15 low levels, can be obtained in hair care formulations through the use of low melting point fatty alcohols. Low melting point fatty alcohols include, for example a variety of branched chain alcohols, short chain alcohols such as those having C₈ to C₁₂ chain length, and unsaturated straight chain alcohols such as oleyl alcohol. Despite these
20 advantages, some low melting point fatty alcohols do not form the thick, gel rheology with cationic surfactants as do the saturated straight chain fatty alcohols, and low melting point fatty alcohols may reduce wet hair feel.

 Hair rinse conditioners have conventionally been based on the
25 combination of a cationic surfactant, which is generally a quaternary ammonium compound such as ditallow dimethyl ammonium chloride, and fatty alcohols, such as cetyl and stearyl alcohols. This combination results in a gel-network structure which provides the compositions with a thick, creamy rheology. However, low melting point fatty alcohols do
30 not form the thick, gel rheology with cationic surfactants as do the saturated straight fatty alcohols, such as cetyl and stearyl alcohols. When a combination of low melting point and waxy alcohols are used, a hair volumizing effect may occur rather than volume reduction and increased alignment. This is because fatty alcohols for hair
35 conditioning, such as cetyl and stearyl alcohols, deposit on the hair in crystal or solid form. These crystalline deposits separate the hair

follicles to provide a volumizing effect. The net effect is reduced glossiness.

In addition some low melting fatty alcohols, e.g. oleyl alcohol, reduces the consumer preferred pleasing wet hair feel and perception of spreading through the hair that is provided by conventional creme hair rinses.

It has now been found that hair conditioning compositions can be provided in the form of a product with a thickened, cream emulsion or gel-type rheology having excellent wet hair feel, spreadability, and rinseability, as well as providing glossiness, hair alignment, and volume reduction, and especially dry combing benefits, through the use of certain low melting point fatty alcohols plus certain water soluble, nonionic, polyoxyethylene and/or polyoxypropylene polymers. In addition selection of particular polyoxyethylene and/or polyoxypropylene polymers having the molecular weights outlined below, also minimizes formulation problems, e.g. stringiness. The invention hereof is described in the sections below.

It is an object of this invention to provide hair care compositions that enhance hair shine and hair alignment, and can reduce hair volume, without causing the hair to become greasy or waxy feeling or to have a dirty or coated appearance.

It is desirable to provide such a composition, as described above in a thickened form, such as a cream emulsion or gel, which can be easily applied and rinsed from the hair. It is a further object of this invention to provide such a hair care composition that has an aesthetically pleasing wet hair feel and perception of spreading upon application to the hair, and especially has dry combing advantages.

It is further desirable to provide a method for conditioning hair in accordance with the above compositions.

These and other objects and benefits of the present invention as may be set forth herein as may now or later become apparent to those skilled in the art can be provided according to the invention which is described herein.

The invention hereof can comprise, consist of, or consist essentially of the essential elements described herein as well as any of the preferred or other optional ingredients described herein.

All percentages herein are by weight of the composition unless otherwise indicated. All ratios are weight ratios unless otherwise indicated. Unless otherwise indicated, all percentages, ratios, and levels of ingredients referred to herein are based on the actual amount
5 of the ingredient, and do not include solvents, fillers, or other materials which may be combined with the ingredient in commercially available products.


All documents referred to herein, including all patents, all patent applications and all articles, are hereby incorporated herein by
10 reference in their entirety unless otherwise indicated.

SUMMARY OF THE INVENTION

The present invention relates to hair care compositions that provide enhanced gloss, alignment, and dry combing, as well as volume reduction to the hair, with low or reduced greasy, oily hair feel, while
15 being formulated in an emulsion having a thick, cream-type rheology with excellent spreading, perception of spreading, and wet hair feel. In particular, the present hair care composition comprises:

(a) from about 0.1% to about 10%, by weight, preferably from about 0.1% to about 5%, more preferably from about 0.25% to about
20 1%, of a monohydric, fatty alcohol having a melting point of 30°C or lower;

(b) from about 0.1% to about 10%, by weight, preferably from about 0.2% to about 5%, more preferably from about 0.5% to about 3%, of a polymer of ethylene oxide, propylene oxide, and mixtures thereof,
25 having the general formula:



wherein R is selected from the group consisting of H, methyl, and mixtures thereof; and n has an average value of from about 2,000 to
30 about 14,000, preferably from about 5,000 to about 9,000, more preferably from about 6,000 to about 8,000;

(c) from 0% to about 20%, by weight, of a conditioning agent selected from the group consisting of cationic surfactants, cationic polymers, nonvolatile silicones, nonvolatile hydrocarbons, saturated
35 C₁₄ to C₂₂ straight chain fatty alcohols, nonvolatile hydrocarbon esters, and mixtures thereof; and

(d) from about 50% to about 99.8%, by weight, water.


The present invention also relates to methods for conditioning hair by applying of an effective amount of the composition to the hair.

DETAILED DESCRIPTION OF THE INVENTION

5 The present invention relates to a hair conditioning composition comprising:

(a) from about 0.1% to about 10%, by weight, preferably from about 0.1% to about 5%, more preferably from about 0.25% to about 1%, of a monohydric, fatty alcohol having a melting point of 30°C or
10 lower, said fatty alcohol being preferably selected from the group consisting of unsaturated straight chain fatty alcohols, saturated branched chain fatty alcohols, saturated C₈-C₁₂ straight chain alcohols, and mixtures thereof;

(b) from about 0.1% to about 10%, by weight, preferably from
15 about 0.2% to about 5%, more preferably from about 0.5% to about 3%, of a polymer of ethylene oxide, propylene oxide, and mixtures thereof, having the general formula:



20 wherein R is selected from the group consisting of H, methyl, and mixtures thereof; and n has an average value of from about 2,000 to about 14,000, preferably from about 5,000 to about 9,000, more preferably from about 6,000 to about 8,000;

(c) from 0% to about 20%, by weight, of a conditioning agent
25 selected from the group consisting of cationic surfactants, cationic polymers, nonvolatile silicones, nonvolatile hydrocarbons, saturated C₁₄ to C₂₂ straight chain fatty alcohols, nonvolatile hydrocarbon esters, and mixtures thereof; and

(d) from about 50% to about 99.8%, by weight, water.

30 The essential ingredients as well as a variety, but non-exclusive, list of preferred and optional ingredients are described below.

Nonvolatile, Low Melting Point Fatty Alcohol

The compositions of the present invention comprise from about 0.1% to about 10%, by weight, preferably from about 0.1% to about 5%,
35 more preferably from about 0.25% to about 1%, of a nonvolatile low melting point fatty alcohol.

The fatty alcohols hereof have a melting point of 30°C or less, preferably about 25°C or less, more preferably about 22°C or less.

The unsaturated fatty alcohols hereof are also nonvolatile. By nonvolatile what is meant is they have a boiling point at 1.0
5 atmospheres of at least about 260°C, preferably at least about 275°C, more preferably at least about 300°C.

Suitable fatty alcohols include unsaturated monohydric straight chain fatty alcohols, saturated branched chain fatty alcohols, saturated C₈-C₁₂ straight chain fatty alcohols, and mixtures thereof. The
10 unsaturated straight chain fatty alcohols will typically have one degree of unsaturation. Di- and tri- unsaturated alkenyl chains may be present at low levels, preferably less than about 5% by total weight of the unsaturated straight chain fatty alcohol, more preferably less than about 2%, most preferably less than about 1%.

15 Preferably, the unsaturated straight chain fatty alcohols will have an aliphatic chain size of from C₁₂-C₂₂, more preferably from C₁₂-C₁₈, most preferably from C₁₆-C₁₈. Especially preferred alcohols of this type include oleyl alcohol and palmitoleic alcohol.

The branched chain alcohols will typically have aliphatic chain
20 sizes of from C₁₂-C₂₂, preferably C₁₄-C₂₀, more preferably C₁₆-C₁₈. Exemplary branched chain alcohols for use herein include isostearyl alcohol, octyl dodecanol, and octyl decanol.

Examples of saturated C₈-C₁₂ straight chain alcohols include octyl alcohol, caprylic alcohol, decyl alcohol, and lauryl alcohol.

25 The low melting point fatty alcohols hereof are used at a level of from about 0.1% to about 10%, by weight of the composition, more preferably from about 0.1% to about 5%, most preferably from about 0.25% to about 1%.

The present compositions are preferably limited to levels of
30 monohydric saturated straight chain fatty alcohols, such as cetyl alcohol and stearyl alcohol, and other waxy fatty alcohols having melting points above 45°C, of no more than about 5%, by weight of the composition, preferably no more than about 4% since the presence of such waxy fatty alcohols can adversely affect the shine benefits of the present
35 invention. However, it may be desirable to use waxy fatty alcohols for their conditioning benefits.

Water Soluble, Nonionic, Polymers of Ethylene
Oxide and Propylene Oxide

The compositions of the present invention comprise from about 0.1% to about 10%, more preferably from about 0.2% to about 5%, and most preferably from about 0.5% to about 3% of a polymer of ethylene oxide and/or propylene oxide.

The polymers of the present invention are characterized by the general formula:



wherein R is selected from the group consisting of H, methyl, and mixtures thereof. When R is H, these materials are polymers of ethylene oxide, which are also known as polyethylene oxides, polyoxyethylenes, and polyethylene glycols.

When R is methyl, these materials are polymers of propylene oxide, which are also known as polypropylene oxides, polyoxypropylenes, and polypropylene glycols. When R is methyl, it is also understood that various positional isomers of the resulting polymers can exist.

In the above structure, n has an average value of from about 2,000 to about 14,000, preferably from about 5,000 to about 9,000, more preferably from about 6,000 to about 8,000.

Polyethylene glycol polymers useful herein that are especially preferred are PEG-2M wherein R equals H and n has an average value of about 2,000 (PEG 2-M is also known as Polyox WSR® N-10 from Union Carbide and as PEG-2,000); PEG-5M wherein R equals H and n has an average value of about 5,000 (PEG 5-M is also known as Polyox WSR® N-35 and Polyox WSR® N-80, both from Union Carbide and as PEG-5,000 and Polyethylene Glycol 300,000); PEG-7M wherein R equals H and n has an average value of about 7,000 (PEG 7-M is also known as Polyox WSR® N-750 from Union Carbide); PEG-9M wherein R equals H and n has an average value of about 9,000 (PEG 9-M is also known as Polyox WSR® N-3333 from Union Carbide); and PEG-14 M wherein R equals H and n has an average value of about 14,000 (PEG 14-M is also known as Polyox WSR® N-3000 from Union Carbide.)

Other useful polymers include the polypropylene glycols and mixed polyethylene/polypropylene glycols.

All percentages describing the polymers in this section of the description herein, are by weight, unless otherwise specified.

5

Water

The compositions of the present invention comprise from about 50% to about 99.8%, by weight, water. The water phase can optionally include other liquid, water-miscible or water-soluble solvents such as lower alkyl alcohols, e.g. C₁-C₅ alkyl monohydric alcohols, preferably
10 C₂-C₃ alkyl alcohols. However, the liquid fatty alcohol must be miscible in the aqueous phase of the composition. Said fatty alcohol can be naturally miscible in the aqueous phase or can be made miscible through the use of cosolvents or surfactants.

The composition of the present invention is an emulsion, having
15 viscosity at 25°C of at least about 5,000 cP preferably from about 8,000 cP to about 50,000 cP, more preferably from about 15,000 cP to about 35,000 cP. Viscosity is determined by a Brookfield RVT, at 20 RPM.

The compositions of the present invention preferably have a pH of from about 2.5 to about 7, more preferably from about 3 to about 6.8,
20 most preferably from about 3.5 to about 6.5. Higher pH can be utilized as long as the composition retains a viscosity of at least about 8,000 cP at 25°C.


Additional Conditioning Agents

The compositions of the present invention can also comprise one
25 or more additional conditioning agents, such as those selected from the group consisting of cationic surfactants, cationic polymers, nonvolatile silicones (including soluble and insoluble silicones), nonvolatile hydrocarbons, saturated C₁₄ to C₂₂ straight chain fatty alcohols, nonvolatile hydrocarbon esters, and mixtures thereof. Preferred
30 conditioning agents are cationic surfactants, cationic polymers, saturated C₁₄ to C₂₂ straight chain fatty alcohols, and silicones (especially insoluble silicones). The components hereof can comprise from 0% to about 20%, preferably, from about 0.1% to about 20%, more preferably from about 0.5% to about 10%, of additional conditioning
35 agents.

Cationic Surfactants

Cationic surfactants useful in compositions of the present invention, contain amino or quaternary ammonium moieties. The cationic surfactant will preferably, though not necessarily, be insoluble in the compositions hereof. Cationic surfactants among those useful herein are disclosed in the following documents, all incorporated by reference herein: M.C. Publishing Co., McCutcheon's, Detergents & Emulsifiers, (North American edition 1979); Schwartz, et al., Surface Active Agents, Their Chemistry and Technology, New York: Interscience Publishers, 1949; U.S. Patent 3,155,591, Hilfer, issued November 3, 1964; U. S. Patent 3,929,678, Laughlin et al., issued December 30, 1975; U. S. Patent 3,959,461, Bailey et al., issued May 25, 1976; and U. S. Patent 4,387,090, Bolich, Jr., issued June 7, 1983.

Among the quaternary ammonium-containing cationic surfactant materials useful herein are those of the general formula:



wherein R_1 - R_4 are independently an aliphatic group of from about 1 to about 22 carbon atoms or an aromatic, alkoxy, polyoxyalkylene, alkylamido, hydroxyalkyl, aryl or alkylaryl group having from about 1 to about 22 carbon atoms; and X is a salt-forming anion such as those selected from halogen, (e.g. chloride, bromide), acetate, citrate, lactate, glycolate, phosphate nitrate, sulfate, and alkylsulfate radicals. The aliphatic groups may contain, in addition to carbon and hydrogen atoms, ether linkages, and other groups such as amino groups. The longer chain aliphatic groups, e.g., those of about 12 carbons, or higher, can be saturated or unsaturated. Especially preferred are di-long chain (e.g., di C_{12} - C_{22} , preferably C_{16} - C_{18} , aliphatic, preferably alkyl). di-short chain (e.g., C_1 - C_3 alkyl, preferably C_1 - C_2 alkyl) quaternary ammonium salts,

Salts of primary, secondary and tertiary fatty amines are also suitable cationic surfactant materials. The alkyl groups of such amines preferably have from about 12 to about 22 carbon atoms, and may be substituted or unsubstituted. Such amines, useful herein, include stearamido propyl dimethyl amine, diethyl amino ethyl stearamide,

dimethyl stearamine, dimethyl soyamine, soyamine, myristyl amine, tridecyl amine, ethyl stearylamine, N-tallowpropane diamine, ethoxylated (with 5 moles of ethylene oxide) stearylamine, dihydroxy ethyl stearylamine, and arachidylbehenylamine. Suitable amine salts
5 include the halogen, acetate, phosphate, nitrate, citrate, lactate, and alkyl sulfate salts. Such salts include stearylamine hydrochloride, soyamine chloride, stearylamine formate, N-tallowpropane diamine dichloride and stearamidopropyl dimethylamine citrate. Cationic amine
10 surfactants included among those useful in the present invention are disclosed in U.S. Patent 4,275,055, Nachtigal, et al., issued June 23, 1981, incorporated by reference herein.

Cationic surfactants are preferably utilized at levels of from about 0.1% to about 10%, more preferably from about 0.25% to about 5%, most preferably from about 0.5% to about 2%, by weight of the
15 composition.

Cationic Polymer Conditioning Agent

The compositions of the present invention can also comprise one or more cationic polymer conditioning agents. The cationic polymer conditioning agents will preferably be water soluble. Cationic polymers
20 are typically used in the same ranges as disclosed above for cationic surfactants.

By "water soluble" cationic polymer, what is meant is a polymer which is sufficiently soluble in water to form a substantially clear solution to the naked eye at a concentration of 0.1% in water (distilled
25 or equivalent) at 25°C. Preferably, the polymer will be sufficiently soluble to form a substantially clear solution at 0.5% concentration, more preferably at 1.0% concentration.

As used herein, the term "polymer" shall include materials whether made by polymerization of one type of monomer or made by
30 two (i.e., copolymers) or more types of monomers.

The cationic polymers hereof will generally have a weight average molecular weight which is at least about 5,000, typically at least about 10,000, and is less than about 10 million. Preferably, the molecular weight is from about 100,000 to about 2 million. The cationic
35 polymers will generally have cationic nitrogen-containing moieties such as quaternary ammonium or cationic amino moieties, and mixtures thereof.

The cationic charge density is preferably at least about 0.1 meq/gram, more preferably at least about 1.5 meq/gram, even more preferably at least about 1.1 meq/gram, most preferably at least about 1.2 meq/gram. Cationic charge density of the cationic polymer can be determined according to the Kjeldahl Method. Those skilled in the art will recognize that the charge density of amino-containing polymers may vary depending upon pH and the isoelectric point of the amino groups. The charge density should be within the above limits at the pH of intended use.

Any anionic counterions can be utilized for the cationic polymers so long as the water solubility criteria is met. Suitable counterions include halides (e.g., Cl, Br, I, or F, preferably Cl, Br, or I), sulfate, and methylsulfate. Others can also be used, as this list is not exclusive.

The cationic nitrogen-containing moiety will be present generally as a substituent, on a fraction of the total monomer units of the cationic hair conditioning polymers. Thus, the cationic polymer can comprise copolymers, terpolymers, etc. of quaternary ammonium or cationic amine-substituted monomer units and other non-cationic units referred to herein as spacer monomer units. Such polymers are known in the art, and a variety can be found in the CTFA Cosmetic Ingredient Dictionary, 3rd edition, edited by Estrin, Crosley, and Haynes, (The Cosmetic, Toiletry, and Fragrance Association, Inc., Washington, D.C., 1982).

Suitable cationic polymers include, for example, copolymers of vinyl monomers having cationic amine or quaternary ammonium functionalities with water soluble spacer monomers such as acrylamide, methacrylamide, alkyl and dialkyl acrylamides, alkyl and dialkyl methacrylamides, alkyl acrylate, alkyl methacrylate, vinyl caprolactone, and vinyl pyrrolidone. The alkyl and dialkyl substituted monomers preferably have C₁-C₇ alkyl groups, more preferably C₁-C₃ alkyl groups. Other suitable spacer monomers include vinyl esters, vinyl alcohol (made by hydrolysis of polyvinyl acetate), maleic anhydride, propylene glycol, and ethylene glycol.

The cationic amines can be primary, secondary, or tertiary amines, depending upon the particular species and the pH of the composition. In general, secondary and tertiary amines, especially tertiary amines, are preferred.

Amine-substituted vinyl monomers can be polymerized in the amine form, and then optionally can be converted to ammonium by a quaternization reaction. Amines can also be similarly quaternized subsequent to formation of the polymer. For example, tertiary amine
5 functionalities can be quaternized by reaction with a salt of the formula R'X wherein R' is a short chain alkyl, preferably a C₁-C₇ alkyl, more preferably a C₁-C₃ alkyl, and X is an anion which forms a water soluble salt with the quaternized ammonium.

Suitable cationic amino and quaternary ammonium monomers
10 include, for example, vinyl compounds substituted with dialkylaminoalkyl acrylate, dialkylaminoalkyl methacrylate, monoalkylaminoalkyl acrylate, monoalkylaminoalkyl methacrylate, trialkyl methacryloxyalkyl ammonium salt, trialkyl acryloxyalkyl ammonium salt, diallyl quaternary ammonium salts, and vinyl quaternary ammonium monomers having cyclic cationic
15 nitrogen-containing rings such as pyridinium, imidazolium, and quaternized pyrrolidone, e.g., alkyl vinyl imidazolium, alkyl vinyl pyridinium, alkyl vinyl pyrrolidone salts. The alkyl portions of these monomers are preferably lower alkyls such as the C₁-C₃ alkyls, more preferably C₁ and C₂ alkyls. Suitable amine-substituted vinyl
20 monomers for use herein include dialkylaminoalkyl acrylate, dialkylaminoalkyl methacrylate, dialkylaminoalkyl acrylamide, and dialkylaminoalkyl methacrylamide, wherein the alkyl groups are preferably C₁-C₇ hydrocarbyls, more preferably C₁-C₃ alkyls.


The cationic polymers hereof can comprise mixtures of monomer
25 units derived from amine- and/or quaternary ammonium-substituted monomer and/or compatible spacer monomers.

Suitable cationic hair conditioning polymers include, for example: copolymers of 1-vinyl-2-pyrrolidone and 1-vinyl-3-methylimidazolium salt (e.g., chloride salt) (referred to in the industry by the Cosmetic,
30 Toiletry, and Fragrance Association, "CTFA", as Polyquaternium-16), such as those commercially available from BASF Wyandotte Corp. (Parsippany, NJ, USA) under the LUVIQUAT tradename (e.g., LUVIQUAT FC 370); copolymers of 1-vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate (referred to in the industry by CTFA as
35 Polyquaternium-11) such as those commercially available from Gaf Corporation (Wayne, NJ, USA) under the GAFQUAT tradename (e.g., GAFQUAT 755N); cationic diallyl quaternary ammonium-containing

polymers, including, for example, dimethyldiallylammonium chloride homopolymer and copolymers of acrylamide and dimethyldiallylammonium chloride, referred to in the industry (CTFA) as Polyquaternium 6 and Polyquaternium 7, respectively; and mineral acid salts of amino-alkyl esters of homo- and co-polymers of unsaturated carboxylic acids having from 3 to 5 carbon atoms, as described in U.S. Patent 4,009,256, incorporated herein by reference.

Other cationic polymers that can be used include polysaccharide polymers, such as cationic cellulose derivatives and cationic starch derivatives.

Cationic polysaccharide polymer materials suitable for use herein include those of the formula:



wherein: A is an anhydroglucose residual group, such as a starch or cellulose anhydroglucose residual, R is an alkylene oxyalkylene, polyoxyalkylene, or hydroxyalkylene group, or combination thereof, R₁, R₂, and R₃ independently are alkyl, aryl, alkylaryl, arylalkyl, alkoxyalkyl, or alkoxyaryl groups, each group containing up to about 18 carbon atoms, and the total number of carbon atoms for each cationic moiety (i.e., the sum of carbon atoms in R₁, R₂ and R₃) preferably being about 20 or less, and X is an anionic counterion, as previously described.

Cationic cellulose is available from Amerchol Corp. (Edison, NJ, USA) in their Polymer JR® and LR® series of polymers, as salts of hydroxyethyl cellulose reacted with trimethyl ammonium substituted epoxide, referred to in the industry (CTFA) as Polyquaternium 10. Another type of cationic cellulose includes the polymeric quaternary ammonium salts of hydroxyethyl cellulose reacted with lauryl dimethyl ammonium-substituted opoxide, referred to in the industry (CTFA) as Polyquaternium 24. These materials are available from Amerchol Corp. (Edison, NJ, USA) under the tradename Polymer LM-200®.

Other cationic polymers that can be used include cationic guar gum derivatives, such as guar hydroxypropyltrimonium chloride (commercially available from Celanese Corp. in their Jaguar R series). Other materials include quaternary nitrogen-containing cellulose ethers

(e.g., as described in U.S. Patent 3,962,418, incorporated by reference herein), and copolymers of etherified cellulose and starch (e.g., as described in U.S. Patent 3,958,581, incorporated herein by reference.)

As discussed above, the cationic polymer hereof is water soluble.

- 5 This does not mean, however, that it must be soluble in the composition. Preferably however, the cationic polymer is either soluble in the composition, or in a complex coacervate phase in the composition formed by the cationic polymer and anionic material. Complex coacervates of the cationic polymer can be formed with anionic
10 surfactants or with anionic polymers that can optionally be added to the compositions hereof (e.g., sodium polystyrene sulfonate).

Silicone Conditioning Agents

- The compositions hereof can also include nonvolatile soluble or insoluble silicone conditioning agents. By soluble what is meant is that
15 the silicone conditioning agent is miscible with the aqueous carrier of the composition so as to form part of the same phase. By insoluble what is meant is that the silicone forms a separate, discontinuous phase from the aqueous carrier, such as in the form of an emulsion or a suspension of droplets of the silicone.


- 20 The silicone hair conditioning agent will be used in the compositions hereof at levels of from about .05% to about 10% by weight of the composition, preferably from about 0.1% to about 6%, more preferably from about 0.5% to about 5%, most preferably from about 0.5% to about 3%.

- 25 Soluble silicones include silicone copolyols, such as dimethicone copolyols, e.g. polyether siloxane-modified polymers, such as polypropylene oxide, polyethylene oxide modified polydimethylsiloxane, wherein the level of ethylene and/or propylene oxide sufficient to allow solubility in the composition.

- 30 Preferred, however, are insoluble silicones. The insoluble silicone hair conditioning agent for use herein will preferably have viscosity of from about 1,000 to about 2,000,000 centistokes at 25°C, more preferably from about 10,000 to about 1,800,000, even more preferably from about 100,000 to about 1,500,000. The viscosity can be
35 measured by means of a glass capillary viscometer as set forth in Dow Corning Corporate Test Method CTM0004, July 20, 1970.

Suitable insoluble, nonvolatile silicone fluids include polyalkyl siloxanes, polyaryl siloxanes, polyalkylaryl siloxanes, polyether siloxane copolymers, and mixtures thereof. Other insoluble, nonvolatile silicone fluids having hair conditioning properties can also be used. The term "nonvolatile" as used herein shall mean that the silicone has a boiling point of at least about 260°C, preferably at least about 275°C, more preferably at least about 300°C. Such materials exhibit very low or no significant vapor pressure at ambient conditions. The term "silicone fluid" shall mean flowable silicone materials having a viscosity of less than 1,000,000 centistokes at 25°C. Generally, the viscosity of the fluid will be between about 5 and 1,000,000 centistokes at 25°C, preferably between about 10 and about 300,000 centistokes.

Silicone fluids hereof also include polyalkyl or polyaryl siloxanes with the following structure:



wherein R is alkyl or aryl, and x is an integer from about 7 to about 8,000 may be used. "A" represents groups which block the ends of the silicone chains.

The alkyl or aryl groups substituted on the siloxane chain (R), or at the ends of the siloxane chains (A) may have any structure as long as the resulting silicones remain fluid at room temperature, are hydrophobic, are neither irritating, toxic nor otherwise harmful when applied to the hair, are compatible with the other components of the composition, are chemically stable under normal use and storage conditions, and are capable of being deposited on and of conditioning hair.

Suitable A groups include methyl, methoxy, ethoxy, propoxy, and aryloxy. The two R groups on the silicone atom may represent the same group or different groups. Preferably, the two R groups represent the same group. Suitable R groups include methyl, ethyl, propyl, phenyl, methylphenyl and phenylmethyl. The preferred silicones are polydimethyl siloxane, polydiethylsiloxane, and polymethylphenylsiloxane. Polydimethylsiloxane is especially preferred.

The nonvolatile polyalkylsiloxane fluids that may be used include, for example, polydimethylsiloxanes. These siloxanes are available, for example, from the General Electric Company in their ViscasilR and SF 96 series, and from Dow Corning in their Dow
5 Corning 200 series.

The polyalkylaryl siloxane fluids that may be used, also include, for example, polymethylphenylsiloxanes. These siloxanes are available, for example, from the General Electric Company as SF 1075 methyl phenyl fluid or from Dow Corning as 556 Cosmetic
10 Grade Fluid.

Especially preferred, for enhancing the shine characteristics of hair, are highly arylated silicones, such as highly phenylated polyethyl silicone having refractive indices of about 1.46 or higher, especially about 1.52 or higher. When these high refractive index
15 silicones are used, they should be mixed with a spreading agent, such as a surfactant or a silicone resin, as described below to decrease the surface tension and enhance the film forming ability of the material.

The polyether siloxane copolymers that may be used include, for example, a polypropylene oxide modified polydimethylsiloxane (e.g., Dow Corning DC-1248) although ethylene oxide or mixtures of ethylene oxide and propylene oxide may also be used. The ethylene oxide and polypropylene oxide level should be sufficiently low to prevent solubility in the composition hereof.
20

References disclosing suitable silicone fluids include U.S. Patent 2,826,551, Geen; U.S. Patent 3,964,500, Drakoff, issued June 22, 1976; U.S. Patent 4,364,837, Pader; and British Patent 849,433, Woolston. All of these patents are incorporated herein by reference. Also incorporated herein by reference is Silicon
25 Compounds distributed by Petrarch Systems, Inc., 1984. This reference provides an extensive (though not exclusive) listing of suitable silicone fluids.

Another silicone hair conditioning material that can be especially useful in the silicone conditioning agents is insoluble
35 silicone gum. The term "silicone gum", as used herein, means polyorganosiloxane materials having a viscosity at 25°C of greater than or equal to 1,000,000 centistokes. Silicone gums are described

by Petrarch and others including U.S. Patent 4,152,416, Spitzer et al., issued May 1, 1979 and Noll, Walter, Chemistry and Technology of Silicones, New York: Academic Press 1968. Also describing silicone gums are General Electric Silicone Rubber Product Data
5 Sheets SE 30, SE 33, SE 54 and SE 76. All of these described references are incorporated herein by reference. The "silicone gums" will typically have a mass molecular weight in excess of about 200,000, generally between about 200,000 and about 1,000,000. Specific examples include polydimethylsiloxane,
10 (polydimethylsiloxane) (methylvinylsiloxane) copolymer, poly(dimethylsiloxane) (diphenyl siloxane)(methylvinylsiloxane) copolymer and mixtures thereof.

Preferably the silicone hair conditioning agent comprises a mixture of a polydimethylsiloxane gum, having a viscosity greater
15 than about 1,000,000 centistokes and polydimethylsiloxane fluid having a viscosity of from about 10 centistokes to about 100,000 centistokes, wherein the ratio of gum to fluid is from about 30:70 to about 70:30, preferably from about 40:60 to about 60:40.

An optional ingredient that can be included in the silicone
20 conditioning agent is silicone resin. Silicone resins are highly crosslinked polymeric siloxane systems. The crosslinking is introduced through the incorporation of trifunctional and tetrafunctional silanes with monofunctional or difunctional, or both, silanes during manufacture of the silicone resin. As is well
25 understood in the art, the degree of crosslinking that is required in order to result in a silicone resin will vary according to the specific silane units incorporated into the silicone resin. In general, silicone materials which have a sufficient level of trifunctional and tetrafunctional siloxane monomer units (and hence, a sufficient level
30 of crosslinking) such that they dry down to a rigid, or hard, film are considered to be silicone resins. The ratio of oxygen atoms to silicon atoms is indicative of the level of crosslinking in a particular silicone material. Silicone materials which have at least about 1.1 oxygen atoms per silicon atom will generally be silicone resins
35 herein. Preferably, the ratio of oxygen:silicon atoms is at least about 1.2:1.0. Silanes used in the manufacture of silicone resins include monomethyl-, dimethyl-, trimethyl-, monophenyl-, diphenyl-, methyl-

phenyl-, monovinyl-, and methylvinyl-chlorosilanes, and tetra-chlorosilane, with the methyl-substituted silanes being most commonly utilized. Preferred resins are offered by General Electric as GE SS4230 and SS4267. Commercially available silicone resins will generally be supplied in a dissolved form in a low viscosity volatile or nonvolatile silicone fluid. The silicone resins for use herein should be supplied and incorporated into the present compositions in such dissolved form, as will be readily apparent to those skilled in the art.

10 Silicone resins can enhance deposition of silicone on the hair and can enhance the glossiness of hair with high refractive index volumes.

Background material on silicones including sections discussing silicone fluids, gums, and resins, as well as manufacture of silicones, can be found in Encyclopedia of Polymer Science and Engineering, Volume 15, Second Edition, pp 204-308, John Wiley & Sons, Inc., 1989, incorporated herein by reference.

15 Silicone materials and silicone resins in particular, can conveniently be identified according to a shorthand nomenclature system well known to those skilled in the art as "MDTQ" nomenclature. Under this system, the silicone is described according to presence of various siloxane monomer units which make up the silicone. Briefly, the symbol M denotes the monofunctional unit $(\text{CH}_3)_3\text{SiO}_{1.5}$; D denotes the difunctional unit $(\text{CH}_3)_2\text{SiO}$; T denotes the trifunctional unit $(\text{CH}_3)\text{SiO}_{1.5}$; and Q denotes the quadri- or tetra-functional unit SiO_2 . Primes of the unit symbols, e.g., M', D', T', and Q' denote substituents other than methyl, and must be specifically defined for each occurrence. Typical alternate substituents include groups such as vinyl, phenyls, amines, hydroxyls, etc. The molar ratios of the various units, either in terms of subscripts to the symbols indicating the total number of each type of unit in the silicone (or an average thereof) or as specifically indicated ratios in combination with molecular weight complete the description of the silicone material under the MDTQ system. Higher relative molar amounts of T, Q, T' and/or Q' to D, D', M and/or M' in a silicone resin is indicative of higher levels of crosslinking. As

discussed before, however, the overall level of crosslinking can also be indicated by the oxygen to silicon ratio.

The silicone resins for use herein which are preferred are MQ, MT, MTQ, MQ and MDTQ resins. Thus, the preferred silicone
5 substituent is methyl. Especially preferred are MQ resins wherein the M:Q ratio is from about 0.5:1.0 to about 1.5:1.0 and the average molecular weight of the resin is from about 1000 to about 10,000.

Other Ingredients

The compositions herein can contain a variety of other optional
10 components suitable for rendering such compositions more cosmetically or aesthetically acceptable or to provide them with additional usage benefits. Such conventional optional ingredients are well-known to those skilled in the art.

A wide variety of additional ingredients can be formulated into
15 the present composition. These include: other conditioning agents; hair-hold polymers; deterative surfactants such as anionic, nonionic, amphoteric, and zwitterionic surfactants; additional thickening agents and suspending agents such as xanthan gum, guar gum, hydroxyethyl cellulose, methyl cellulose, hydroxyethylcellulose, starch and starch
20 derivatives; viscosity modifiers such as methanolamides of long chain fatty acids such as cocomonooethanol amide; crystalline suspending agents; pearlescent aids such as ethylene glycol distearate; preservatives such as benzyl alcohol, methyl paraben, propyl paraben and imidazolidinyl urea; polyvinyl alcohol; ethyl alcohol; pH adjusting
25 agents, such as citric acid, sodium citrate, succinic acid, phosphoric acid, sodium hydroxide, sodium carbonate; salts, in general, such as potassium acetate and sodium chloride; coloring agents, such as any of the FD&C or D&C dyes; hair oxidizing (bleaching) agents, such as hydrogen peroxide, perborate and persulfate salts; hair reducing
30 agents, such as the thioglycolates; perfumes; sequestering agents, such as disodium ethylenediamine tetra-acetate; and polymer plasticizing agents, such as glycerin, disobutyl adipate, butyl stearate, and propylene glycol. Such optional ingredients generally are used individually at levels from about 0.01% to about 10.0%, preferably from
35 about 0.05% to about 5.0% by weight of the composition.

METHOD OF USE

The hair care compositions of the present invention are used in conventional ways to provide the conditioning and other benefits of the

present invention. Such method of use depends upon the type of composition employed but generally involves application of an effective amount of the product to the hair, which may then be rinsed from the hair (as in the case of hair rinses) or allowed to remain on the hair (as in the case of gels, lotions, and creams). "Effective amount" means an amount sufficient enough to provide a dry combing benefit. In general, from about 1g to about 50g is applied to the hair on the scalp. The composition is distributed throughout the hair, typically by rubbing or massaging the hair and scalp. Preferably, the composition is applied to wet or damp hair prior to drying of the hair. After such compositions are applied to the hair, the hair is dried and styled in accordance with the preference of the user. In the alternative, the composition is applied to dry hair, and the hair is then combed or styled in accordance with the preference of the user.

EXAMPLES

The following examples illustrate the present invention. It will be appreciated that other modifications of the present invention within the skill of those in the hair care formulation art can be undertaken without departing from the spirit and scope of this invention.

All parts, percentages, and ratios herein are by weight unless otherwise specified. Some components may come from suppliers as dilute solutions. The levels given reflect the weight percent of the active material, unless otherwise specified.

EXAMPLES I-V

Hair rinse compositions of the present invention are prepared as follows:

<u>Component (Wt.%)</u>	<u>Ex. I</u>	<u>Ex. II</u>	<u>Ex. III</u>	<u>Ex. IV</u>	<u>Ex. V</u>
Oleyl Alcohol	1.0	1.0	1.0	1.0	0.25
PEG-7M ¹	2.0	1.0		1.0	-
PEG-2M ²	-	-	1.0	-	1.00
Polydimethylsiloxane ³	4.20	4.2	4.2	4.2	4.2
Silicone Resin ⁴	0.25	0.25	0.25	0.25	-
Pentaphenyl Trimethyl Trisiloxane ⁵	0.38	0.38	0.38	0.38	-
DL Panthenol	0.04	0.04	0.04	0.04	.04
Panthenyl Ethyl Ether	0.34	0.34	0.34	0.34	.34
Fragrance	0.3	0.35	0.35	0.35	.35
Kathon™ CG ⁶	0.03	0.03	0.03	0.03	.03

			21		
	Cetyl Alcohol	1.2	1.8	1.8	1.2
	Stearyl Alcohol	0.8	1.2	1.2	0.8
	Ditallow Dimethyl				
	Ammonium Chloride	0.75	0.75	0.75	0.75
5	Stearamidopropyl				
	Dimethylamine	1.0	1.0	1.0	1.0
	Glycerol Monostearate	0.25	0.25	0.25	0.25
	Citric Acid	0.19	0.22	0.22	0.22
	Hydroxyethyl Cellulose	-	0.25	0.25	-
10	Mineral Oil	-	-	-	-
	Water	q.s	q.s	q.s	q.s

- 1 PEG-7M is Polyethylene Glycol where n has an average value of about 7,000 and is commercially available under the tradename of Polyox WSR® N-750 from Union Carbide.
- 15 2 PEG-2M is Polyethylene Glycol where n has an average value of about 2,000 and is commercially available under the tradename of Polyox WSR® N-10 from Union Carbide.
- 3 An 85%/15% (wt. basis) mixture of D5 Cyclomethicone and dimethicone gum (weight average molecular weight of about 400,000 to about 600,000).
- 20 4 Polytrimethyl hydrosilylsilicate, added as a 50 wt. % solution in decamethylcyclopentasiloxane, General Electric Silicone Products, SS 4320.
- 25 5 Dow Corning 705, Dow Corning Corp. (Midland, MI, USA).
- 6 Methylchloroisothiazoline (and) methylisothiazoline, a preservative from Rohm & Haas Co., (Philadelphia, PA, USA).

EXAMPLES VI and VII

30 Hair rinse compositions of the present invention are prepared as follows:

	<u>Component (Wt. %)</u>	<u>Ex. VI</u>	<u>Ex. VII</u>
	Oleyl Alcohol	0.25	1.0
	PEG-7M ¹	1.0	-
35	PEG-14M ²	-	0.25
	Polydimethylsiloxane ³	4.20	4.2
	Silicone Resin ⁴	0.25	0.25

22

	Pentaphenyl Trimethyl		
	Trisiloxane ⁵	0.38	0.38
	DL Panthenol	0.04	0.04
	Panthenyl Ethyl Ether	0.34	0.34
5	Fragrance	0.35	0.35
	Kathon™ CG ⁶	0.03	0.03
	Cetyl Alcohol	1.8	1.8
	Stearyl Alcohol	1.2	1.2
	Ditallow Dimethyl		
10	Ammonium Chloride	0.75	0.75
	Stearamidopropyl		
	Dimethylamine	1.0	1.0
	Glycerol Monostearate	0.25	0.25
	Citric Acid	0.22	0.22
15	Hydroxyethyl Cellulose	0.25	0.25
	Water	q.s	q.s

- 1 PEG-7M is Polyethylene Glycol where n has an average value of about 7,000 and is commercially available under the tradename of
- 20 Polyox WSR® N-750 from Union Carbide.
- 2 PEG-14M is Polyethylene Glycol where n has an average value of about 14,000 and is commercially available under the trade name of Polyox WSR® N-3000 from Union Carbide.
- 3 An 85%/15% (wt. basis) mixture of D5 Cyclomethicone and
- 25 dimethicone gum (weight average molecular weight of about 400,000 to about 600,000).
- 4 Polytrimethyl hydrosilylsilicate, added as a 50 wt. % solution in decamethylcyclopentasiloxane, General Electric Silicone Products, SS 4320.
- 30 5 Dow Corning 705, Dow Corning Corp. (Midland, MI, USA).
- 6 Methylchloroisothiazoline (and) methylisothiazoline, a preservative from Rohm & Haas Co., (Philadelphia, PA, USA).

For each of the above examples, a silicone premix is prepared

35 by mixing: the polydimethylsiloxane, silicone resin, and pentaphenyl trimethyltrisiloxane in a tank.


For Examples I - V, the PEG is added to ambient water and thereafter mixed. Then this mixture is heated to about 80°C. The following ingredients are then added, sequentially, with agitation between each addition: ditallow dimethyl ammonium chloride, oleyl alcohol, cetyl alcohol, stearyl alcohol, stearamidopropyl dimethylamine, and glyceryl monostearate. Cool the batch to about 49°C. Then the following ingredients are added, sequentially, with agitation between each addition: silicone premix, citric acid, panthenol, panthenyl ethyl ether, perfume, and Kathon™ CG. Cool the composition to a temperature of from about 25°C to about 35°C.

For Examples II and VII, the hydroxyethyl cellulose is added to ambient water and agitated. PEG-7M or PEG-14M is added and the mixture is heated to about 80°C. The following ingredients are then added, sequentially, with agitation between each addition: ditallow dimethyl ammonium chloride, cetyl alcohol, stearyl alcohol, stearamidopropyl dimethylamine, and glyceryl monostearate. Cool the batch to about 49°C. Then the following ingredients are added, sequentially, with agitation between each addition: silicone premix, citric acid, panthenol, panthenyl ethyl ether, perfume, Kathon™ CG, and oleyl alcohol. Cool the composition to a temperature of from about 25°C to about 35°C.

For Examples II, III and V, the hydroxyethyl cellulose is added to ambient water and agitated. The PEG-2M or PEG-7M is added and the mixture is heated to about 80°C. The following ingredients are then added, sequentially, with agitation between each addition: ditallow dimethyl ammonium chloride, cetyl alcohol, stearyl alcohol, stearamidopropyl dimethylamine, and glyceryl monostearate. Cool the batch to about 49°C. Then the following ingredients are added, sequentially, with agitation between each addition: silicone premix, citric acid, panthenol, panthenyl ethyl ether, perfume, Kathon™ CG, and oleyl alcohol. Cool the composition to a temperature of from about 25°C to about 35°C.

What is claimed is:

1. A hair care composition comprising:
 - (a) from 0.1% to 10% by weight, of a low melting point fatty alcohol having a melting point of 30°C or lower;
 - (b) from 0.1% to 10% by weight, of a polymer of ethylene oxide, propylene oxide, and mixtures thereof, having the formula:



wherein R is selected from the group consisting of H, methyl, and mixtures thereof; and n has an average value of from 2,000 to 14,000;

- (c) from 0% to 20% by weight, of a conditioning agent selected from the group consisting of cationic surfactants, cationic polymers, nonvolatile silicones, nonvolatile hydrocarbons, saturated C₁₄ to C₂₂ straight chain fatty alcohols, nonvolatile hydrocarbon esters, and mixtures thereof; and
 - (d) from 50% to 99.8% by weight, water.
2. The composition of Claim 1 wherein the low melting point fatty alcohol is selected from the group consisting of unsaturated C₈-C₂₂ straight chain fatty alcohols, saturated C₁₂-C₁₈ branched chain fatty alcohols, saturated C₈-C₁₂ straight chain fatty alcohols, and mixtures thereof, preferably wherein the fatty alcohol is selected from the group consisting of unsaturated C₁₆-C₁₈ straight chain fatty alcohols, C₁₄-C₁₈ branched chain fatty alcohols, and mixtures thereof, more preferably wherein the low melting point fatty alcohol has a melting point of 25°C or lower, and most preferably wherein the fatty alcohol is oleyl alcohol.
3. The composition of Claim 1 wherein n has an average value of from 5,000 to 9,000.
4. The composition of Claim 3 wherein the low melting point fatty alcohol is selected from the group consisting of unsaturated C₈-C₂₂ straight chain fatty alcohols, saturated C₁₂-C₁₈ branched chain fatty alcohols, saturated C₈-C₁₂ straight chain fatty alcohols, and mixtures thereof, preferably wherein the fatty alcohol is selected from the group consisting of unsaturated C₁₆-C₁₈ straight chain fatty alcohols,


C₁₄-C₁₈ branched chain fatty alcohols, and mixtures thereof, more preferably wherein the low melting point fatty alcohol has a melting point of 25°C or lower, and most preferably wherein the fatty alcohol is oleyl alcohol.

5. The composition of Claim 1 wherein R is H and n has an average value of from 5,000 to 9,000, preferably wherein n has an average value of from 6,000 to 8,000.

6. The composition of Claim 5 wherein the low melting point fatty alcohol is selected from the group consisting of unsaturated C₈-C₂₂ straight chain fatty alcohols, saturated C₁₂-C₁₈ branched chain fatty alcohols, saturated C₈-C₁₂ straight chain fatty alcohols, and mixtures thereof, preferably wherein the fatty alcohol is selected from the group consisting of unsaturated C₁₆-C₁₈ straight chain fatty alcohols, C₁₄-C₁₈ branched chain fatty alcohols, and mixtures thereof, more preferably wherein the low melting point fatty alcohol has a melting point of 25°C or lower, and most preferably wherein the fatty alcohol is oleyl alcohol.

7. The composition of Claim 1 comprising:

- (a) from 0.25% to 1% by weight, of a low melting point fatty alcohol having a melting point of 30°C or lower;
- (b) from 0.5% to 3% by weight, of a polymer of ethylene oxide having the formula:



wherein R is H and n has an average value of from 5,000 to 9,000; and

(c) from 0.1% to 20% by weight, of a conditioning agent selected from the group consisting of cationic surfactants, cationic polymers, nonvolatile silicones, nonvolatile hydrocarbons, saturated C₁₄ to C₂₂ straight chain fatty alcohols, nonvolatile hydrocarbon esters, and mixtures thereof, preferably wherein the conditioning agent is selected from the group consisting of cationic surfactants, saturated C₁₄ to C₂₂ straight chain fatty alcohols, and mixtures thereof.

8. The composition of Claim 7 wherein the composition comprises from 0.5% to 2% by weight of a quaternary ammonium cationic surfactant,

preferably wherein the quaternary ammonium surfactant is selected from the group consisting of ditallow dimethyl quaternary ammonium compound, monotallow trimethyl quaternary ammonium compound, dicetyl dimethyl quaternary ammonium compound, and mixtures thereof.

9. The composition of Claim 8 wherein the composition comprises from 0.5% to 5% of a saturated C₁₄ to C₂₂ straight chain fatty alcohol.

10. A method for conditioning hair comprising applying an effective amount of the composition of any of Claims 1 through 9 to the hair for enhanced dry combing.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 95/00983

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A61K7/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP,A,0 262 885 (DEL LABORATORIES INCORPORATED) 6 April 1988 see example 1 ---	1-10
A	PATENT ABSTRACTS OF JAPAN vol. 17 no. 644 (C-1134) ,10 August 1993 & JP,A,05 201841 (KANEBO LTD) 27 January 1992, see abstract ---	1-10
A	US,A,3 687 855 (HALPERN) 29 August 1972 see the whole document ---	1-10
A	WO,A,91 16878 (THE PROCTER & GAMBLE COMPANY) 14 November 1991 see page 32, line 7 - page 33, line 33; claims 1-12 see page 20, line 5 - line 10 ---	1-10
-/--		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- * "A" document defining the general state of the art which is not considered to be of particular relevance
- * "E" earlier document but published on or after the international filing date
- * "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- * "O" document referring to an oral disclosure, use, exhibition or other means
- * "P" document published prior to the international filing date but later than the priority date claimed

- * "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- * "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- * "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * "&" document member of the same patent family

Date of the actual completion of the international search

9 May 1995

Date of mailing of the international search report

24. 05. 95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+ 31-70) 340-3016

Authorized officer

Fischer, J.P.

INTERNATIONAL SEARCH REPORT

Intern. Application No
PCT/US 95/00983

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB,A,2 218 334 (SANDOZ LTD) 15 November 1989 see the whole document ---	1-10
A	DE,A,19 61 152 (KOLMAR LABORATORIES INC.) 25 June 1970 see example SALBE -----	1-10

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 95/00983

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-262885	06-04-88	AU-B- 596867	17-05-90
		AU-A- 7815287	31-03-88

US-A-3687855	29-08-72	AT-B- 320827	25-02-75
		AT-B- 318151	25-09-74
		AU-B- 464861	26-08-75
		AU-A- 2490371	03-08-72
		AU-B- 462545	12-06-75
		AU-A- 2957171	07-12-72
		BE-A- 767573	24-11-71
		CH-A- 561674	15-05-75
		CH-A- 564348	31-07-75
		CH-A- 561774	15-05-75
		DE-A- 2123551	16-11-72
		DE-A- 2105057	10-08-72
		DE-A- 2166215	03-05-73
		FR-A- 2124097	22-09-72
		FR-A, B 2138295	05-01-73
		GB-A- 1315461	02-05-73
		GB-A- 1319413	06-06-73
		NL-A- 7101478	08-08-72
		NL-A- 7108024	13-12-72
		US-A- 3671545	20-06-72

WO-A-9116878	14-11-91	US-A- 5100657	31-03-92
		AU-B- 644174	02-12-93
		AU-A- 7852091	27-11-91
		CN-A- 1056050	13-11-91
		EP-A- 0595804	11-05-94
		NZ-A- 237998	23-12-93

GB-A-2218334	15-11-89	BE-A- 1002266	13-11-90
		CH-A- 679119	31-12-91
		DE-A- 3915617	16-11-89
		FR-A- 2631235	17-11-89
		JP-A- 2017127	22-01-90
		JP-B- 7005473	25-01-95

DE-A-1961152	25-06-70	NONE	

THIS PAGE BLANK (USPTO)